

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form with the insurance policy

Inspection Date: 08/23/11		
Owner Information		
Owner Name: SPINEL CONDOMINIUM ASSOCIATION		Contact Person: CAROL COCOZZA
Address: 379 GABRIEL CIRCLE		Home Phone: _____
City: NAPLES	Zip: 34104	Work Phone: _____
County: COLLIER		Cell Phone: _____
Insurance Company: _____		Policy #: _____
Year of Inception: 1993	# of Stories: 2	Email: _____

I, JOHN D. PIERSON (print name of the individual who actually performed the inspection), personally conducted the inspection of the residence identified on this form and in my professional opinion, all the data reported is true and correct.

1. Building Code: What building code was used to design and build the structure?

- A. 1994 South Florida Building Code (building permit application date of 9/1/1994 or later in Miami-Dade and Broward Counties (also known as the High Velocity Hurricane Zone (HVHZ)).
- B. Building code prior to the 1994 South Florida Building Code (building permit application date of 8/31/1994 or earlier in Miami-Dade and Howard Counties (HVHZ)).
- C. 2001 Florida Building Code (building permit application date of 3/1/2002 or later outside the HVHZ).
- D. Building code prior to the 2001 Florida Building Code (building permit application date of 2/28/2002 or earlier outside the HVHZ).
- E. Unknown or undetermined.

2. Predominant Roof Covering:

Permit Application Date: _____ or Date of Installation: **2006**

- A. At a minimum meets the 2001 Florida Building Code or the 1994 South Florida Building Code and has a Miami-Dade NBC or FBC 2001 Product Approval listing demonstrating compliance with ASTM F 3161 (enhanced film composite) or ASTM D 7158 (Fiberglass or FRP). OR FIC-TAS 100-95 and TIS 107-95, OR FMRC 4470 and/or 4471 (for metal roofs).
- B. Does not meet the above minimum requirements.
- C. Unknown or undetermined.

NOTE: At least one photo documenting the existence of each visible and accessible construction or mitigation attribute marked in Sections 3 through 9 must accompany this form.

3. Roof Deck Attachment: What is the weakest form of roof deck attachment?

- A. Plywood/oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift resistance of 55 psf.
- B. Plywood/OSB roof sheathing with a minimum thickness of 3/16" attached to the roof truss/rafter (spaced a maximum of 24" o.c.) by 8d common nails spaced 6" along the edge and 12" in the field. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift resistance of 103 psf.
- C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" attached to the roof truss/rafter (spaced a maximum of 24" o.c.) by 8d common nails spaced 6" along the edge and 6" in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board. -OR- Any system of screws, nails, adhesives, other decking fastening system or truss/rafter spacing that has an equivalent mean uplift resistance of 182 psf.
- D. Reinforced Concrete Roof Deck.

Inspectors Initials: _____ If Property Address: 379 GABRIEL CIRCLE NAPLES FL 34104

F. Other: _____

i. Unknown or unidentified.

J. No attic access.

4. Roof to Wall Attachment: What is the weakest roof to wall connection?

A. Toe Nails Rafter/truss anchored to top plate of wall using nails driven at an angle through the rafter/truss and attached to the top plate of the wall.

B. Clips Metal attachments on every rafter/truss that are nailed to one side (or both sides in the case of a diamond type clip) of the rafter/truss and attached to the top plate of the wall frame or embedded in the bond beam.

C. Single Wraps Metal Straps must be secured to every rafter/truss with a minimum of 3 nails, wrapping over and securing to the opposite side of the rafter/truss with a minimum of 1 nail. The Strap must be attached to the top plate or the wall frame or embedded in the bond beam in at least one place.

D. Double Wraps Both Metal Straps must be secured to every rafter/truss with a minimum of 3 nails, wrapping over and securing to the opposite side of the rafter/truss with a minimum of 1 nail. Each Strap must be attached to the top plate of the wall frame or embedded in the bond beam in at least one place.

E. Structural Anchor bolts structurally connected or reinforced concrete roof.

F. Other: _____

(i. Unknown or Unidentified

II. No attic access

5. Roof Geometry: What is the roof shape(s)? (Porches or carports that are attached only to the fascia or wall of the host structure and not structurally connected to the main roof system are not considered in the roof geometry determination.)

A. Hip Roof Hip roof (With no other roof shapes greater than 10% of the total building perimeter.

B. Non-Hip Roof Any other roof shape or combination of roof shapes including hip, gable, gambrel, mansard and other roof shapes not including flat roofs.

C. Flat Roof Flat roof shape greater than 100 square feet or 10% of the entire roof: whichever is greater.

6. (Table EQD R-402.2: For roof structures that contain gables, please check the one(s) that apply:

A. (Table EQD R-402.2) are braced at a minimum in accordance with the 2001 Florida Building Code. Does not meet the above minimum requirements.

B. Not applicable, unknown or unidentified.

7. Wall Construction Type: (Check all wall construction types for exterior walls of the structure and percentages for each:

- A. Wood Frame _____
- B. Un-Reinforced Masonry _____
- C. Reinforced Masonry _____ %
- D. Poured Concrete _____
- E. Other: _____

8. Secondary Water Resistant (SWR): (standard underlayment or hot mopped bits are not SWR)

A. SWR Self-adhering polymer modified bitumen roofing underlayment applied directly to the sheathing or to an adhesive SWR barrier (not flange on insulation) applied as a secondary means to protect the dwelling from water intrusion.

B. No SWR

C. Unknown or undetermined.

9. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? (Exterior openings include, but are not limited to: windows, doors, garage doors, skylights, etc. Product approval may be required for opening protection devices without proper rating identification.)

A. All Exterior Openings (Glazed and Unglazed) All exterior openings are fully protected at a minimum with impact resistant coverings, impact resistant doors and/or impact resistant windows units that are listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one or

Inspector's Initials: _____ Property Address 379 GABRIEL CIRCLE NAPLES FL 34104

the following for "Cyclic Pressure and Large Missile Impact". For the HVHZ, systems must have either a Miami-Dade NCJA or FBC Approval marked "For Use in the HVHZ".

- Miami-Dade County Notice or Acceptance (NCJA) 201, 202 and 203. (Large Missile - 9 lb.)
- Florida Building Code Testing Application Standard (TAS) 201, 202 and 203. (Large Missile - 9 lb.)
- American Society for Testing and Materials (ASTM) E 1886 and ASTM F 1996. (Large Missile - 9 lb.)
- Southern Standards Technical Document (SSTD) 12. (Large Missile - 9 lb.)
- For Skylights Only: ASTM E 1886/E 1996. (Large Missile - 4.5 lb.)
- For Garage Doors Only: ANSI/D118.1. (Large Missile - 9 lb.)

B. All exterior openings are fully protected at a minimum with impact resistant coverings, impact resistant doors and/or impact resistant window units that are listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for Cyclic Pressure and Large Missile Impact...

- ASTM E 1886 and ASTM E 1996. (Large Missile - 4.5 lb.)
- SSTD 12. (Large Missile - 4 lb. to 8 lb.)
- For Skylights Only: ASTM E 1886/E 1996. (Large Missile - 2 to 4.5 lb.)

C. All exterior openings are fully protected at a minimum with impact resistant coverings, impact resistant doors and/or impact resistant window units that are listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for Cyclic Pressure and Small Missile Impact...

- Miami-Dade County NCJA 201, 202 and 203; (Small Missile - 2 grams)
- Florida Building Code TAS 201, 202 and 203. (Small Missile - 2 grams)
- ASTM E 1886 and ASTM E 1996. (Small Missile - 2 grams)
- SSTD 12. (Small Missile - 2 grams)

D. All exterior openings are fully protected with windborne debris protection devices that cannot be identified as Miami-Dade or Florida Building Code (FBC) product approved. This does not include plywood/JSB or plywood alternatives (see Appendix H).

All Glazed Exterior Openings

- E. All glazed exterior openings are fully protected at a minimum with impact resistant coverings and/or impact resistant window units that meet the requirements of one of the standards listed in Answer A of this question. (Large Missile - 9 lb.)
- F. All glazed exterior openings are fully protected at a minimum with impact resistant coverings and/or impact resistant window units that meet the requirements of one of the standards listed in Answer B of this question. (Large Missile - 2 lb. - 8 lb.)
- G. All glazed exterior openings are fully protected at a minimum with impact resistant coverings and/or impact resistant window units that meet the requirements of one of the standards listed in Answer C of this question. (Small Missile - 2 grams)
- H. All glazed exterior openings are covered with plywood/JSB meeting the requirements of Section 1609 and Table 1609.1.4 of the 2004 FBC (with 2006 supplements).
- I. All glazed exterior openings are fully protected with windborne debris protection devices that cannot be identified as Miami-Dade or FBC product approved. This does not include plywood/JSB or other plywood alternatives that do not meet Answer I (see Answer K).

~~None or Some Glazed~~

- J. At least one glazed exterior opening does not have windborne debris protection.
- K. No glazed exterior openings have windborne debris protection. This includes plywood/JSB or plywood alternative systems that do not meet Answer I.
- L. Unknown or undetermined.

Inspectors Initials: _____ Property Address: 379 GABRIEL CIRCLE NAPLES FL 34104

